

Cart Assembly Instructions

Model # CART-SIZ26 / CART-SIZ32 / CART-SIZ40

CART-SF432 / CART-SF538

Step 1: Remove parts from the carton and remove all protective film prior to assembly. (2 people recommended for assembly)

Step 2: With the Bottom Panel (#2) positioned upside down on a protective surface, attach the 2 pcs Locking Casters (#1) and 2 pcs Casters (#1B) using 4 pcs of 10x24 screws (H-1) and 4 pcs of Locking Washers (H-2) per caster.

Step 3: Attach the Tank Bracket Assembly (#10 -11) to the underside of the Bottom Panel (#2) using 2 pcs of 10x24 screws (H-1).

Step 4: Turn the Bottom Panel (#2) upright and then attach the inference Bracket (#12) to the Bottom Panel (#2) with 4 pcs of 10x24 screws (H-1).

Step 5: Attach the Right and Left Side Panels (#3A & #3B) by using 6 pcs of the 10x24 screws (H-1).

Step 6: Attach the Lower Back Panel (#5A) to the Left & Right Side Panels using 6 pcs of 10x24 screws (H-1).

Step 7: Attach Upper Back Panel (5B) to the Left & Right Side Panels using 6 pcs of 10x24 screws (H-1).

Step 8: Lay the Front Doors on a flat surface and attach the Front Door Handle (#8) to each Front Door (#6) using 2 pcs of 10x24 screws (H-1), for each handle.

Step 9: (Best done with an assistant) Attach the Front Strut Assembly (#4) between the front of each Side Panel and secure with 6 pcs of 10x24 screws (H-1).

Step 10: Place the Front Doors (#6) into the cart assembly, by first inserting the Bottom Pin of the door into the hole located on the Bottom Panel. Then insert the Upper Pin of the door into the hole located on the underside of the Front Strut (#4). Follow same procedure for both doors.

Step 11: Attach the Side Shelf (#7) to each Side Panel by using 4 pcs 10x24 screws (H-1).

Step 12: Attach the Lower Magnetic Catch (#9) by using 2 pcs of 10x24 screws (H-1) to the center of the Bottom Panel (#2). You may have to adjust both magnets to make sure they have good contact with both doors.

Step 13: Finally, the barbecue is ready to be installed into the cart. Once installed, secure the barbecue head with 2 pcs 10x24 screws (H-1) through the holes that are on each side (underneath the grates inside bbq on right and left side toward front).

Note: Some adjustments may be needed to obtain proper placement or level positioning in the cart. Make sure to tighten all the screws with a screwdriver once the cart is level.

Note: The Propane tank is held in position by the Tank Bracket Screw (#11).

SAFETY WARNING: If applicable, grill transformer should be mounted on the OUTSIDE of the Cart.

No.	Description	Qty.	No.	Description	Qty.
1A	Locking Caster	2	6	Front Doors	2
1B	Caster	2	7	Double Side Shelf	2
2	Bottom Panel	1	8	Front Door Handle	2
3A	Right Side Panel	1	9	Magnetic Catch	2
3B	Left Side Panel	1	10	Tank Bracket	1
4	Front Strut Assembly	1	11	Tank Screw	1
5A	Lower Back Panel	1	12	Interference Bracket	1
5B	Upper Back Panel	1	H-1	10 x 24 Screw	64
			H-2	Lock Washers	16

